

RAPID TILL STRIP TILL SYSTEM



SCHLAGEL


FOR FARMERS  BY FARMERS



RAPID TILL

THE SMART CHOICE FOR STRIP TILL

Lightweight and low draft, the Rapid Till is perfect for applying fertilizer (dry, liquid, or anhydrous ammonia) in the fall or spring. Able to travel up to 10 m.p.h., this unit can cover large acreages in a short amount of time—and because of its low weight and draft, it can even be utilized by smaller tractors! Quality construction, ease of maintenance, and excellent performance make the Rapid Till a smart choice for a wide range of farmers.



BENEFITS

CONNECT A PLANTER

Using the available lift assist and link arms option, you can connect a planter right behind your Rapid Till to complete a one-pass tilling and planting operation.

HIGH RESIDUE

Thanks to finger row cleaner wheels that move residue, not soil, this unit excels at handling high-residue situations. Its intelligent design allows trash to flow easily through the row unit components with minimal disturbance and minimal plugging.

Row cleaners are adjustable for height and width, allowing you to decide how wide of an area is swept clean. When adjusting for width, the front remains in the same relationship to the front coulter, ensuring a clean strip..

GAUGE WHEELS

Residue is left on the surface, and a strip of soil remains exposed so the soil warms quicker in the spring. The rear gauge wheels are adjustable for width, and options are available for building a berm.



DESIGNED FOR

Reduced Tillage

UNIQUE FEATURES

UNIT ADJUSTMENTS

All unit adjustments are accomplished by pins, ensuring every adjustment is easy, consistent, and precise. A common bolt pattern allows a wide choice of shanks to fit the unit (including many aftermarket shank options), and running depths range from 2" to 11" to meet most farmers' needs. An easy-to-reach shear bolt also provides rock protection.

IDEAL CROPS

Any Row Crop

SPECS

STANDARD EQUIPMENT

The following equipment is included with your Rapid Till:

- Adjustable row cleaners
- 20" flat coulter
- 3/4" x 4" shank
- 17" wavy coulters (2)
- 16" dual-wheel light packer

OPTIONS

CONFIGURATIONS

Custom configurations are available upon request; add Up to 24 Rows and Row spacing down to 20".

EQUIPMENT COMPATIBILITY

20HP average per row is recommended; actual requirements will vary with options and soil conditions.



SCAN FOR MORE INFORMATION



 **SCHLAGEL**

Our products are simple, yet stalwart, and they're built and tested to ensure they'll be in it for the long haul. Visit our website to locate a trusted Schlagel dealer near you. Have questions? Just give us a call!

www.schlagel.net

307.532.4451

